

ANALOGUE PREAMPLIFIERS & MIXERS/ INSTALLATION PREAMPLIFIERS & MIXERS/ SAM312

Applications

- Gyms
- Licensed venue
- Restaurants
- Leisure venue
- Retail outlets
- Boardrooms and conference centres
- Entertainment music playback
- Education centres
- A / V presentations

Installation Analogue Mixer

SAM312 is an installation mixer in standard rack format. It includes 3 MIC / ST LINE inputs, 2 stereo outputs, 3 band tone control and external MUTE connection port.



Key Features

- 3 input channels, 2 main outputs 19" installation mixer
- 3 MIC / stereo LINE input channel mixer
- Input signal pushbutton selector (MIC / LINE) on back panel
- Dedicated "Low Line" input with adapted sensibility for low level line signal sources, like mp3 players (iPod®, etc.) and laptop computers
- Independent internal assignable phantom power for all MIC inputs
- Direct MIX input allows straight forward connection of further mixers
- Triple tone control (accessible only with screwdriver)
- 2 stereo outputs
- 3 led output level metre
- 2 additional stereo REC outputs (REC1, REC2)
- Mono mode pushbutton
- Headphones general MIX monitoring
- Full remote MUTE control
- Side rack mount ears with 2 possible positions, for front panel alignment with devices in the same rack

Main Technical Specifications	Inputs	3 MIC / Stereo Line selectable via pushbutton			
	Outputs	2 Stereo + 2 REC + 1 Headphones			
	Tone Control	Bass (100 Hz), Mid (2 kHz), Treble (10 kHz)			
	Remote Control	Mute			
	Dimensions / weight	H: 482.6 mm	L: 44 mm	W: 195 mm	2.4 Kg

Accessories

- MPAGE1, desktop paging station
- WPmMIX-T, MICRO+LINE wall panel mixer with talkover function



WPmMIX-T



MPAGE1