

ANALOGUE PREAMPLIFIERS & MIXERS/ INSTALLATION PREAMPLIFIERS & MIXERS/ SAM614T

Applications

- Gyms
- Licensed venue
- Restaurants
- Leisure venue
- Retail outlets
- Boardrooms and conference centres
- Entertainment music playback
- Education centres
- A / V presentations

Installation Analogue Mixer

SAM614T is an installation mixer in standard rack format. It includes a total of 6 inputs (2 MIC inputs, 2 MIC / ST LINE inputs + 2 ST LINE inputs), 2 independent stereo outputs (2 ST zones) , independent 3 band tone control per each output, Talkover (priority) function and external MUTE connection port.



Key Features

- Each channel features signal present (SP) and CLIP indicators
- General phantom power switch located on back panel. Independent internal phantom power assignment to any MIC input
- Triple tone control (accessible only with a screwdriver)
- 2 main stereo outputs with independent volume control
- 3 LED output level metre
- Input channels can be routed to any main output (A,B) or both
- 2 additional stereo REC outputs (REC1, REC2)
- Mono mode selector
- Headphones monitoring of selected output (A or B)
- Integrated, internally configurable TALKOVER. Affects OUT A and REC A
- Built-in, internally programmable TALKOVER. Affects OUT A and REC A

Main Technical Specifications	Channels	6 with independent gain			
	Inputs	2 x MIC + 2 x MIC / Stereo Line + 2 x Stereo Line + 1 x Low Line (mp3, iPod®, Laptops etc.). Each input routable to 2 main outputs			
	Outputs	2 x Stereo + 2 x REC + 1 x Headphones			
	Tone Control	On each Output (Bass, Mid and Treble)			
	Remote Control	Mute			
	Dimensions / weight	H: 482.6 mm	L: 44 mm	W: 195 mm	2.4 Kg

Accessories

- MPAGE1, desktop paging station
- WpMIX-T, MICRO+LINE wall panel mixer with talkover function



WpMIX-T



MPAGE1