Public Address Speakers

PHS20T, PRSIOT, MSP50T

loudspeaker cabinets

PHS2OT, MSP5OT and PRS1OT are products carefully selected for the most extended 100V/70V paging and background music applications, offering durability and optimal speech and music reproduction. All models are manufactured in reinforced ABS and are IP rated and therefore suitable for outdoor superior performance.



PHS2OT Key features

- ABS weatherproof horn loudspeaker
- IP56
- Power tappings (100V) : 15, 7.5, 3.75, 2 W
- 20 W RMS/8 ohms
- Freq response (-3dB): 300Hz 8kHz
- Efficiency: 102 dB SPL 1W/1m
- Dimensions (diameter x depth): 200x233 mm

• 1.3 Kg



PRSIOT Key features

- ABS weatherproof sound projector
- IP55
- Power tappings (100V) : 10, 5, 2.5 W
- Freq response (-3dB): 130Hz 15kHz
- Efficiency: 91 dB SPL 1W/1m
- Dimensions (diameter x depth) :136x220 mm
- 1.6 Kg



MSP5OT Key features

- ABS weatherproof two way musical horn
- IP56
- Power tappings (100V) : 50, 25, 12.5, 9, 4.5, 3.5W
- Freq response (-3dB): 90Hz-20kHz
- Efficiency: 99 dB SPL 1W/1m
- Dimensions (mm): 250x360x320
- 3.9 Kg

Tech. Characteristics	PRSIOT	PHS2OT	MSP50T
	PRS10T	PHS20T	MSP50T
Nominal low impedance		8W	8W
RMS power	10W	20W	50W
Nominal high impedance	100V LINE 10, 5, 2.5W	100V LINE 15W, 7.5W, 3.75W, 2W	100V LINE 50, 25, 12.5, 9, 4.5, 3.5W
		70.7V LINE15W, 7.5W, 3.75W, 2W, 1W	
Frequency response (-6dB)	150Hz – 15kHz	300Hz – 8kHz	70Hz – 20kHz
Sensitivity 1W/1m	91dB	102dB	99dB
Dimensions (diameter x depth)	136x220mm	200x233mm	250x360x320mm
Weight	1.6kg	1.35kg	3.95kg

Applications

General paging and background music reproduction in 100V/70V installations



