

S8015 II

SUBWOOFER



DESCRIPTION

The S8015 II is a compact, high-output, bass reflex subwoofer. The system is equipped with an advanced, hyperventilated 15" RCF precision woofers. It features massive ceramic magnet and high excursion 4" copper voice coil. This new woofer design is the result of the latest refinements in RCF experiences in compact active and passive subwoofer design, resulting in a fast and controlled reproduction of the bass frequency range. Using bass-reflex loading the subwoofer design ensures an efficient acoustic response down to 30 Hz.

The cabinet is designed to achieve tight and maximised output.

The system is able to produce a Max SPL of 133 dB and handles 1000 Watts AES

The Baltic birch plywood enclosure is painted with black, heavy duty, textured epoxy. The front is protected by a strong powder coated metal grille. The cabinet features two Neutrik Speakon™ connectors in a recessed input plate. A M20 pole mount adaptor is provided on the top of the cabinet, integrated hand carry points on the cabinet sides.

MAIN FEATURES

- 15" high-efficiency RCF Precision 4" voice-coil woofer with Inside/Outside Coil Technology
- 133 dB maximum sound pressure level
- Response down to 35 Hz
- Rectangular box enclosure with protective metal grille
- 35 mm standard pole mount in top section of cabinet
- Baltic Birch cabinet painted with black, heavy duty, textured epoxy
- Integrated hand carry points

MAIN APPLICATIONS

- Low Frequency Enhancement
- Music Enhancement
- Special Effects Reinforcement
- Entertainment Systems
- Live Music Reinforcement
- Mid to Large Club Sound Systems

ACOUSTICAL SPECIFICATIONS

Frequency response:	35 Hz ÷ 200 Hz
Max SPL:	133 dB
Sensitivity 1W/1m:	98 dB
Coverage angle:	-
Compression driver:	-
Midrange:	-
Woofers:	15" neo, 4" voice coil
Power handling:	1500W

INPUT SECTION

Input signal (Impedance):	8 Ω
Input connector:	Speakon NL4
Output signal connector:	Speakon NL4

PROCESSOR SECTION

Crossover frequencies:	-
Protections:	-

PHYSICAL

Cabinet:	Baltic birch - Black epoxy coating
Dimensions (HxWxD):	525x 440x 615 mm (20.66"x17.32"x24.21")
Weight:	34 kg (74.8 lbs)
Hardware:	M20, Recessed side handles
Handles:	2 on side
Pole Mount :	only AC PM M20
Colour:	Black epoxy coating



S8015 II



