

# MC 5054

## UNIVERSAL HIGH QUALITY MICROPHONE



### DESCRIPTION

MC 5054 is a condenser microphone with high quality capsule, mounted on a flexible arm 445 mm long, and to be installed on microphone support with XLR connector. It is powered with phantom from 9 V to 52 V and windshield polyurethane foam.

### PART NUMBER

141.15.024


### MAIN FEATURES

- Directional characteristics: uni-directional
- Element type: back Electret Condenser
- Frequency: 50 Hz - 18.000 Hz
- Impedance: 200
- Sensitivity: -65 dB  $\pm$  3 dB (0 dB = 1 V/microbar 1.000 Hz indicated by open circuit).
- Operating voltage: phantom power, 9V ~ 52V DC
- Accessories: windscreen

### MAIN APPLICATIONS

- Conferences
- Interviews
- Audio mixing
- Broadcasting

### DIMENSIONS (All data are in mm)



### SPECIFICATIONS

Microphone type	back Electret Condenser
Directivity	uni-directional
Frequency response	50 Hz $\div$ 18 kHz
Microphone sensitivity	-65 dB $\pm$ 3 dB
Phantom power	yes
Connector	XLR
Operating voltage	9V ~ 52V DC V
Height	540/21.25 mm/inch

