


# CM20DT

6.5" two-way, thin edge ceiling  
loudspeaker, white



The CM20DT 6.5" two-way built-in loudspeaker can be used in 16 ohms or 70/100 volt modes. The high-quality 70/100 volt transformer is equipped with an easy tapping sticker with clear colour indication. The transformer colours are aligned with the cables connecting the Apart Quick Fit connector, a handy installer connector via push terminal.

In 16 ohms use, you can connect up to 4 loudspeakers in parallel on each channel of a standard 4 ohms amplifier. The paintable thin edge grille makes CM20DT the ultimate loudspeaker for design interior integration.

## TECHNICAL SPECIFICATIONS

outside diameter in mm	210	depth in mm	80
cutout in mm	186	loudspeaker system	2-way
woofer size in inch	6.5	woofer cone material	polypropylene
tweeter size in inch	1	mounting system	3 screws
colour	white	100V transformer power taps in watts	20 - 10 - 5
70V transformer power taps in watts	20 - 10 - 5 - 2.5	impedance in ohms	16
low impedance dynamic power in watts	60	SPL 1W/1m in dB	86
max SPL 1m in dB	104	frequency response in Hz	60 - 20K
main construction material	ABS plastic	grille main material	steel
IP rating	50	applicable low impedance	yes
applicable in 100V	yes	Vertical dispersion angle 1000 Hz	180°
Net weight product in kg	1.24		

MORE PICTURES

