

## **SDQ5PIR-BL**

Design loudspeakerset 5," 2 x 30 watts with RC, black



SDQ5PIR is a stereo loudspeaker set with 1 active and 1 passive loudspeaker that stands for reliability, affordability, dynamic music and detailed voice reproduction! The active stereo amplifier loudspeaker has a low distortion high efficiency 5.25" woofer and one output is fed to the second linkable passive loudspeaker.

The SDQ5PIR set can be controlled from the included infrared remote control, via serial commands or via the Apart wall control panels (ACP, ACPL or ACPR) which allow control of power and volume. ACPL and ACPR also allow the addition of external audio inputs. Teachers, lecturers or anyone who is giving a presentation can stop worrying about audio system problems and stay focused on their presentation. All inputs can be gain adjusted, used individually or mixed together. The balanced input allows long signal line without interference. You will not hear any hum or buzz, because there will be no ground loop issues when connecting the SDQ5PIR with notoriously difficult laptops, LCD projectors or interactive white boards.

These loudspeakers will give you a variety of sound possibilities when used in conjunction with a flat screen, projector or smart board. With their magnetic shielding these loudspeakers are the ideal and cost effective audio solution for your classroom, boardrooms or meeting room.

## **TECHNICAL SPECIFICATIONS**

| height in mm                           | 253                | width in mm                    | 180           |
|--|--------------------|--------------------------------|---------------|
| depth in mm                            | 162                | power supply                   | 230 VAC       |
| loudspeaker system                     | 2-way              | woofer size in inch            | 5,25          |
| woofer cone material                   | polypropylene      | tweeter size in inch           | 1             |
| mounting system                        | U-bracket          | colour                         | black / white |
| low impedance dynamic power            | 2 x 30             | SPL 1W/1m in dB                | 86            |
| in watts                               |                    | frequency response in Hz       | 45 - 20K      |
| max SPL 1m in dB                       | 101<br>ABS plastic |                                |               |
|  |                    | grille main material           | steel         |
| main construction material             |                    | active                         | Yes           |
| IP rating                              | 40                 | active                         | 100           |
| ii ruung                               | -0                 | Vertical dispersion angle 1000 | 180°          |
| Horizontal dispersion angle<br>1000 Hz | 180°               | Hz                             |               |
|  |                    |                                |               |
| Net weight product (kg)                | 5,60               |                                |               |



## **MORE PICTURES**









## ACCESSORIES





ACPR Volume control panel with local input for SDQ5PIR

ACPL Volume control panel with local input for SDQ5PIR



ACP Volume control panel for SDQ5PIR