




Projectors... and More!

EIP-UJT100

14,000 Lumens / WUXGA / 3-chip DLP®
"Large Venue" Series Projector

EIP-UJT100

- 14,000 lumens bright and a 2000:1 contrast ratio.
- 3-chip DLP® technology.
- 4 Digital Inputs including HDBaseT and 3G HD-SDI.
- Native WUXGA resolution. Compatible with inputs up-to UXGA and WUXGA.
- Supports analog and digital video input in all color standards up-to 1080p.
- Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions.
- 3D availability with Stereo DVI.
- Wired network monitoring and control.
- Dicom Simulation mode for viewing grayscale images such as X-rays.
- Rear-accessed lamp for ease of maintenance.
- Optional lens cover a range of 0.67 to 6.96:1 Throw ratios.
- Built-in Edge Blending and Image Warping and Corner Keystone Correction.
- Built-in Picture in Picture and Picture by Picture.
- Security bar. Kensington® MicroSaver® security slot. PIN lock.
- Select between 115V and 230V.
- *3 year projector warranty.



Included Accessories:

Quick Start Guide, Owner's Manual on CD-ROM, VGA Computer Input Cable (Dsub15 to Dsub15), 6.0 ft (1.8 m) Detachable Power Cords x 2
Remote Control (with 2 AA Batteries), Wired Remote Cable (MiniStereo to MiniStereo)

Optional Accessories:

Replacement Lamp, ATA-Style Case with Wheels and Telescoping Handle, Ceiling Mount, Ceiling Post and Plate. Stacking Frame

Specifications: Model EIP-UJT100

Brightness	14,000 ANSI Lumens	Image Signal Resizing	Smart Scaling Technology
Contrast Ratio	2000:1	Image Signal Inputs	
Resolution and Aspect Ratio	WUXGA (1920 x 1200), 16:10	Computer 1	Dsub15 x 1
Color Reproduction	10 bit	Computer 2	5 BNC x 1
Projection Lamp	465 Watts NSH x 2	Digital Video (w/ HDCP)	HDMI x 1
Estimated Lamp Life	up-to 2,500 hours	Digital Video (w/ HDCP)	DVI-D x 1
Total Pixels	6,912,000 (1920 x 1200) x 3	Component Video	RCA x 3
Imaging System	0.96" DMD™ DLP® chip x 3	HDBaseT Lite	RJ45 x 1
Scanning Frequency	Auto: H Sync. 15.63-91.15 kHz, V Sync. 23.98-120 Hz	3D Sync	BNC x 1
Pixel Clock	162 MHz	3G HD-SDI	BNC x 1
Lens	Optional Lenses Available - See lens chart on website	Screen Trigger	DC12V x 2
Lens Specs	Optional Lenses Available - See lens chart on website	Outputs	
Lens Ratios	Optional Lenses Available - See lens chart on website	3D Sync	BNC x 1
Image Diagonal	80-600 in (203.2-1524 cm)	3G HD-SDI	BNC x 1
Image Width	5.6-42.5 ft (1.7-12.9 m)	Fan Noise (Normal / Eco)	48 / 42 dB
Throw Distance	Optional Lenses Available - See lens chart on website	Cabinet Size (HxWxD) - excluding legs	10.6 x 19.8 x 25.0 in (26.9 x 50.2 x 63.5 cm)
Projector Elevation Adjustment (legs)	up-to 5°	Weight	81.5 lb (37 kg)
Vertical Keystone Correction	Digital: up-to 20° Up or Down	Packaged Size (HxWxD)	17.2 x 26.6 x 31.8 in (43.6 x 67.5 x 80.7 cm)
Horizontal Keystone Correction	Digital: up-to 35° Left or Right	Packaged Weight	92.5 lb (42 kg)
Image Orientation	Normal, Reversed, Inverted	Operating Temperature	41-95°F (5-35°C)
Local Control / Power Management	Full Function / Auto Shutdown	Electrical Safety Compliance	IEC / UL / cUL
Remote Control / Service	Wireless / Wired x 1 / USB-B x 1	Electromagnetic Compatibility	FCC Class A, CE Mark
Remote Control / RS-232 Control	MiniStereo x 1 / Dsub9 x 1	Power Requirements	100-240V AC, 50/60 Hz
LAN Port	RJ45 x 1	Power Consumption	0.5 W in Eco Standby mode, up-to 1230W
Computer Input in Pixels	up-to 1600x1200 (4:3), 1920x1200 (16:10)	Heat	up-to 4,198 BTU/hr
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	Security Facilities	Security Bar, Kensington® Security Slot
Analog Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA	UPC	4571194677270
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	User Maintenance	Replace Lamp / Replace Filter
Digital Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA	Limited Warranty: to the original end use customer only	
Video Input Analog	480i/p, 576i/p	Projector	*3 years / 6000 hours
Video Input Digital	480p, 575p, 720p, 1080i/p	Lamp	*1 year / 500 hours use - original lamp *90 days / 500 hours - replacement lamp (whichever occurs first)

Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.
EIKI® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.

Specifications subject to change without notice. ©2015 Eiki International Inc. Issued Apr. 28, 2015
Eiki International Inc., 30251 Esparanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, Email: usa@eiki.com
In Canada: 9170 County Rd. 93, Suite 304, Midland ON, L4R 4K4. Tel: 800-563-3454, Email: canada@eiki.com