

## VS-21DT

2x1 4K60 4:2:0 HDCP 2.2 HDMI Auto Switcher over HDBaseT | HDMI | HDCP Compliant | HDBaseT | 4K/60 UHD (4:2:0) | HDCP 2.2 Compatible





VS-21DT is a high-performance automatic switcher for 4K, HDBaseT, HDMI 1.4, HDCP 2.2 video signals. Offering priority and last-connected switching options, it automatically switches according to the selected switching scheme based on active video signal detection

## **FEATURES**

Max. Data Rate - 8.91Gbps (2.97Gbps per data channel)

Max. Resolution - 4K@60Hz (4:2:0)

HDMI 1.4 & HDCP 2.2 Compliant

Supports up to 40m reach at 4K@60Hz (4:2:0)

Kramer Equalization and re-Klocking Technology

**HDTV** Compatible

3D Pass-Though



## **TECHNICAL SPECIFICATIONS**

Inputs 2 HDMI On female HDMI connectors

Outputs 1 HDBT On an RJ-45 connector

Video Max. Data Rate 8.91Gbps (2.97Gbps per graphic channel)

Max. Resolution 4K@60Hz (4:2:0)

Standards Compliance HDCP 2.2 (does not support conversion to HDCP 1.4),

**HDMI 1.4** 

User Interface Controls DIP-switches for selecting switching mode (Priority/Last Connected),

contact closure connectors for remote control switches

Indicators Active input, switching mode (Priority/Last Connected) and ON

Power Source 5V DC

Consumption 1A

REGULATORY CERTIFICATION:

EMC EN 55032;IEC 60950-1(ed.2);IEC 60950-1(ed.2)am1;IEC 60950-1(ed.2)am2

Environmental Conditions

Operating Temperature 0° to +40°C (32° to 104°F)

Storage Temperature -40° to +70°C (-40° to 158°F)

Humidity 10% to 90%, RHL non-condensing

Accessories Included 5V DC power adapter

PRODUCT DIMENSION:

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.5kg (1.1lbs) approx

