

PAGENETDN

DIGITAL CONTROLS

EclerNet Dante™ Paging Station & Control Touch-Screen



PRODUCT OVERVIEW

PAGENETDN is a programmable Paging Station with dual audio output: Dante™ (digital) and analogue (balanced). This way, its control features and its microphone signal can be used for paging together with any EclerNet digital matrix, no matter whether it supports Dante™ or not: MIO4040DN, MIMO88, MIMO88SG and MIMO1212SG.

At the same time it shares the same control features as the WPNETTOUCH, and can be programmed to control one or more networked EclerNet devices; it can even control a full installation, a project combining a multitude of different EclerNet devices: MIMO4040DN, MIMO88, MIMO88SG, MIMO1212SG digital matrices, NXA series digital audio managers, DUO-NET PLAYER units, etc. It is fully programmable through the EclerNet Manager application (*).

(*) Refer to the EclerNet Manager Application manual for more information. The EclerNet Manager application is available for download at www.ecler.com.

It comes with a desktop console design, including a gooseneck microphone and a 10" capacitive touch screen panel that can show and manage the User Control Panels for paging and for the control of networked EclerNet devices, VEO video devices and third-party devices.

KEY FEATURES

- EclerNet control device, with the ability to execute EclerNet projects on its internal engine, acting as a server and / or client of UCP panels
- 10 "capacitive touch screen
- Ethernet network connection
- POE or external power supply (multi-plug universal PSU included)
- VESA75 and desktop mounting systems included

- Digital touchscreen embedded control panel, including the same features as the WPNETTOUCH device:
 - 10.1" IPS display (1280 x 800 pixels)
 - Capacitive & multitouch touch panel
- PoE DC supply compatible
- External power supply compatible: external & universal PSU included + multi-plug AC set
- Ethernet Base-Tx 10/100Mb interface
- Flexo type gooseneck microphone included, XLR connector with safety flap (to avoid microphone unwanted removal)
- Audio transport using Dante™, 2 channels:
 - Dante™ channel #1 used for microphone signal transmission
 - Dante™ channel #2 used for AUX input signal transmission
- Phantom Power available for the MIC input
- MIC out, analogue balanced signal, that makes the PAGNETDN unit compatible for paging in combination with devices that don't support Dante™ in a native way, as the MIMO88, MIMO88SG and MIMO1212SG
- AUX input, stereo LINE, RCA connectors. The incoming signal is converted to mono and sent to the network using Dante™ channel #2. It can be used to connect an external audio source (like a media player) and inject its signal to the network in Dante™ format
- Paging features based on programmable UCP control panels
- EclerNet control device, with the ability to execute EclerNet projects on its internal engine, acting as a server and / or client of UCP panels

APPLICATIONS


- Commercial
- Hospitality
- Education
- Corporate
- Sports and wellness


MECHANICAL SPECIFICATIONS

MIC INPUT	
Microphone type	Removable gooseneck condenser microphone (eMCN1)
Polar pattern	Unidireccional
Microphone freq. response	50Hz – 18kHz (-10dB)
Phantom Voltage	48VDC, ON/OFF by internal JUMPER
Output level with eMCN1 MICROPHONE	-5dBV @ 94dB SPL with ADJ MAX. -10dBV @ 94dB SPL with ADJ MID. -20dBV @ 94dB SPL with ADJ MIN.
HPF	100Hz 12dB/oct ON/OFF by internal JUMPER
LINE INPUT	
Connector	RCA
Signal	Line level, L + R
Nominal input level	-10dBV
Gain adjust	-20dBV / 0dBV
Input impedance	>10kΩ
DANTE™ AUDIO INTERFACE	
Dante Network Tx channels	2
Latency	1 / 2 / 5 ms (selectable)
Connector	RJ45
AUDIO OUTPUTS	
Microphone output signal Connector	Balanced, analog
Output level	Phoenix connector (symmetric) 0dBV
System	
CPU	RK3128 quad core processor, clocked 1.6G
RAM	1GB
ROM	8GB
Screen	
Size	10,1" IPS
Resolution	1280x800
Contrast ratio	1300
Brightness	300cdm2
Screen scale / Display area	16:9 / 218x135mm
Backlight	LED
Touch-panel	Capacitive multi-touch
Network & Connectivity	
Ethernet	Supports PoE
Ethernet port	Ethernet Base-Tx 10/100Mb / 1GB CAT5e or better up to 100m.
Power	
External power supply voltage	12VDC
Maximum power consumption	12W from 12V External Power Supply Voltage 15W from PoE

	PoE: class 0 802.3af Poe PD compliant
General	
Dimensions (microphone excluded)- WxHxD	295x155x135 mm / 11.6"x6.1"x5.3"
Weight	1.5 kg / 3.3 lbs
AC Power Adapter	100-240VAC 47-63Hz 12V / 2A
Accessories included	
AC power adapter	100-240VAC 47-63Hz 12V / 1.5A, multi-plug
Microphone	Ecler eMCN1

MECHANICAL DIAGRAMS







All product characteristics are subject to variation due to production tolerances. **NEEC AUDIO BARCELONA S.L.** reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications.

Motors, 166-168 08038 Barcelona - Spain - (+34) 932238403 | information@ecler.com |