

DIMAX404K Presentation Matrix

DEXON's All-in-One, 4K Matrix Switchers, 4x4



> **Matrix switch of 4x4**
> **4K inputs, 4K outputs**
> **Up- and down-scaling**
> **Seamless switching**
> **Transition effects**
> **PIP of 2 different inputs**

Intelligent Matrix

DEXON Systems' DIMAX Matrix Switchers are vital components in demanding AV projects where different input signals must be switched to any or multiple outputs. They serve broadcast, digital signage or conference room applications that demand the best equipment in order to deliver a complete solution. DEXON Intelligent Matrix (DIMAX) provides perfect solution with smart features as quality scaling, transition effects and seamless switching. DIMAX Family offers superior design, excellent price/performance balance, brilliant video quality and high reliability tailored to challenging AV projects. Easy installation and usage is guaranteed by DEXON's intuitive man-machine interface.

Main Features

DIMAX404K intelligent matrix is an all-in-one solution provided by a standalone box with the following features:

- Supports 4 HDMI inputs, up to 4K resolution
- Drives 4xHDMI 4K outputs
- High quality scaling up or scaling down of input signals
- Programmable seamless switching
- Attractive transition effects, cross fade switching
- PIP of two different input sources to any output
- Built-in media player
- Full HDCP support for input and output connections
- Embedded and separate analogue audio switching
- RS-232C and RJ45 LAN connectors for remote control
- HTML5 based, easy-to-use graphics user interface for configuration, layout management and scenario handling

DEXON Systems Ltd.



Main Features

Input Signals

- Digital HDMI with HDCP
- L, R audio

Input Signal Specification

HDMI 1.4, YUV 4:4:4, 4:2:2, HDCP 2.2
from 640x480 to 3840x2160 30Hz

Output Signals

- HDMI with HDCP
- L, R audio

Output Signal Specification

HDMI 1.4, YUV 4:4:4, 4:2:2, HDCP 2.2
from 640x480 to 3840x2160 30Hz


Audio Handling

R, L analogue audio inputs and outputs
Audio embedding and de-embedding

Setup and Configuration


- Easy-to-use setup through push buttons and LCD panel
- LAN connection for remote setup
- RS-232C control

Application




System Architecture

DIMAX404K Front Panel



DIMAX404K Back Panel



General

- Dimensions: 435 x 325 x 66 (mm)
- 19" rack-mountable enclosure

Models

	Input signals	Output signals
DIMAX404K	4x HDMI with HDCP 4x Audio	4x HDMI with HDCP 4x Audio

DEXON Systems Ltd.

E-mail: sales@dexonsystems.com Web: <http://www.dexonsystems.com>
Phone: +36 23 422 804 Fax: +36 23 445 199 Address: Baross u. 165. H-2040 Budaörs, Hungary
Copyright © DEXON Systems Ltd. All Rights Reserved